Compac 50

Designed for confined spaces where you have limited space to fit your pump



Whale's Most Slim Line Design

- Includes sleek Whale deck plate with cover
- Tough proven reliable
- High performance (up to 35 ltrs / 9.2 US gals per min)
- Suitable for pumping bilge water saltwater or diesel

5 Year Warranty



It is important to ensure that a vented anti-syphon loop is incorporated in the system

Awards and Accreditations

 Suitable as a primary bilge pump on boats equal to or greater than 12 m (40 ft) accordance with ISO15083

COMPLETE YOUR SYSTEM

Whale high quality bilge accessories including non-return valves, elbows and Y pieces see page 40 - 43



Product Information

Model Specifications

Model Product Code	Compac 50 Thru Deck / Bulkhead BP0350	
Weight	0.9 kg (2 lbs)	
Hose Connections	25 mm (1") Smooth Hose Connections	
Materials	Pump Body: Glass-filled Polypropylene, Clamp Ring: Acetal Diaphragm, Valves and Seals: Nitrile®, Operating Lever: Glass-filled Nylon Gaiter: EPDM, Deck Plate Cover: PBT, Fasteners: Stainless Steel	
Materials In Contact With Fluid	Glass-filled Polypropylene, Nitrile®, Stainless Steel	
Service Kit	AK8035 - Whale Compac 50 - diaphragm, valves and fixings AS0352 - Whale Compac 50 - Rocker Arm + Clamp Plate Kit AS0353 - Whale Compac 50 - Clamping Ring Kit AS0355 - Whale Compac 50 - Handle Assembly AS0356 - Whale Compac 50 - Deckplate Kit	
Accessories	AS0353 - Clamping Ring Kit AS0355 Spare Handle / AS0356 - Deckplate Kit	
Maximum Suction Lift	3 m (10 ft)	
Maximum Discharge Head	4 m (13 . 5 ft)	

120mm	199mm
(4 ¾4)	(7 134g)
Front View	Side View

Performance Data

Suction Lift	1 m (3 ft)
Discharge Head	0,5 m (1,5 ft)
45 Strokes per Minute	32 ltrs (9 US gals)
70 Strokes per Minute	35 ltrs (9.2 US gals)

Note: These specifications are retail items only.

For details of our bulk pack range for boat builders and wholesalers - contact Whale Support, $\,$

